THE DISPLAY CHOICE
OF PROFESSIONALS™

K-A19

An affordable 19” widescreen display designed expressly for home and office environments.

Featuring a crisp contrast and ultra-fast response time, the K-A19 is perfect for today’s high resolution, high speed software applications. The sleek slim bezel design and VESA compatible wall mounts allow for a variety of display options. The K-A19 combines AG Neovo’s award-winning image quality with a widescreen format that is perfect for home or multi-user office environments where both performance and cost are important considerations.

> 19” wide screen format
> WXGA 1440 x 900 resolution
> Slim and sleek design
> Swift 3 ms response time
> Crisp 850:1 contrast ratio
> High 300 cd/m² brightness
> Up to 30° tilt angle
> Easy-to-use control buttons
> Kensington® security socket
> VESA standard wall mount
> Two available colours: black, silver

K-A19

Specifications		K-A19
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments Viewing Angle (H/V) Display Colour Response Time Panel Life Time	TFT LCD 19.0" (483 mm) WXGA 1440 x 900 0.285 mm 300 cd/m² (Typical) 850:1 (Typical) Hard Coating (3H), Anti-glare Treatment 170°/160° (Typical) 16.2M 3 ms (GTG) 40,000 hrs (Minimum)
Frequency (H/V)		H: 31 kHz - 81 kHz V: 55 Hz - 75 Hz
Max. Pixel Clock		135 MHz
Input	Analogue	15-Pin D-Sub
Power	AC-DC Adaptor Power Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 40 W (On) < 2 W (Stand-by) < 1 W (Off)
Plug & Play	VESA	DDC-2B, DPMS
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 90%
Storage Conditions	Temperature Humidity	-20 °C ~ 60 °C 5% ~ 95%
Mounting	VESA FPMPMI	Yes (75 mm)
Tilt	Tilt	-5° ~ +25°
Dimensions	Product (W x H x D) Packaging (W x H x D)	440 x 352 x 207 mm (17.3" x 13.6" x 8.0") 510 x 425 x 145 mm (19.7" x 16.4" x 5.6")
Weight	Product Weight Packaged Product Weight	4.0 kg (8.8 lbs) 5.0 kg (11.0 lbs)
Regulation Approval	Certifications & Compliance	CB, FCC, UL, CUL, TUV, BSMI, CE, Energy Star, GOST, TCO 99, TUV/GS, WEEE, RoHS
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), 15-Pin D-Sub cable, AC power cord, base

Widescreen format allows for greater productivity by enabling two windows to be open at the same time without any overlap

VESA standard wall mount allows for secure mounting almost anywhere

AG neovo

All specifications are subject to change without prior notice.
Copyright © 2008 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.
All other trademarks are the property of their respective owners.
P/C: KA19A0 Version 6.0, 20080530